

PLAYGROUND SAFETY INSPECTION Spring Rocking Equipment Worksheet

General:

Description of units:

1. _____
2. _____
3. _____
4. _____

Yes No N/A Audit

Yes	No	N/A	Audit
			General (<i>ASTM F 2373-11 Section 9.4</i>) (<i>CPSC #325-10 Section 5.3.7</i>)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Seats are designed to minimize use by more than the intended number of users
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Seats are not less than 12" high when unloaded and at rest
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Seats are not more than 16" high when unloaded and at rest
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Multiple occupancy spring rockers with opposing seats are 37" apart from center of seat to center of seat.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Each occupant position is provided with handgrips
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Each occupant position is provided with footrest
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Handgrip length is a maximum of 3" per hand
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Handgrips are a minimum of .6" and a Maximum of 1.2"
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Footrest are 3.5" wide
			Use Zones (<i>ASTM F 2373-11 Section 11.6</i>)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	In indoor and outdoor supervised settings the minimum use zone is 36"
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	In settings with unlimited access settings the minimum use zone is 72".

Maintenance Condition:

Good, Needs repair

Priority:

Priority 1 Priority 2 Priority 3 Compliant

Comments: _____
